

# MAHARASHTRA POLLUTION CONTROL BOARD

REGIONAL OFFICE-KALYAN

Phone : 0251-2310167 /2310212

Fax : 0251-2310192

Email : rokalyan@mpcb.gov.in

Visit At <http://mpcb.gov.in>



Sidhivinayak Sankul 3rd floor, Near Oak  
Baug, Station Road,

Kalyan - 421301

## Green/SSI

Consent No: MPCB/ROK/KCA/O/CC- 465

Date: 13-01-2012

Consent to **Operate under** Section 25 / 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. PAWAN MACHENERIES PVT LTD.,  
Plot No.56, Atgaon Indl. Complex,  
Vill. Atgaon, Tal :Shahapur,  
Dist. Thane.

Located in the area declared under the provisions of the Water Act / Air act and Authorization under the provisions of Management, Handling & Transboundary Movement) Rules 2008 to subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to **Operate** is granted for a period valid up to 30/11/2017.

1. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Railway Track Materials & Allied Items	10	MT/M
2	Fabrication	10	MT/M
	Sealing & Packing Machinery	100	Pieces/M

(Without use of any Chemical, Pickling, Galvanizing, Painting activity)

## 2. CONDITIONS UNDER WATER ACT:

- The daily quantity of trade effluent from the factory shall be Nil.
- The daily quantity of sewage effluent from the factory shall not exceed 2.0 M<sup>3</sup>.
- Trade Effluent : Nil
- Trade Effluent Disposal: Nil
- Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids	Not to exceed	100	mg/l.
(2) BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated effluent shall be connected to a septic tank followed by soak pit which shall be got cleaned periodically. The overflow shall be used on land for gardening purpose.

